According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2014-2 RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Epoxy constituents

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : HUNTSMAN ADVANCED MATERIALS (UK) LIMITED

Address : Ickleton Road, Duxford, Cambridgeshire

CB22 4XQ United Kingdom

Telephone : +41 61 299 20 41

E-mail address of person responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333 Australia: 1800 786 152

New Zealand: 0800 767 437 USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :







Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Prevention:

Precautionary statements : P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/

doctor.

P391 Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE)

1,4-bis(2,3 epoxypropoxy)butane

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

	CAS-No.	Classification	Concent
	EC-No. Index-No.		ration
			(% w/w)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

	Registration number		
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 603-073-00-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 30 - < 50
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE)	-	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - < 20
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute dermal toxicity: 1,100 mg/kg	>= 2.5 - < 3
Reaction mass of bis(2,3- epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene- 1,2,4-tricarboxylate	Not Assigned -	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 2; H361f STOT RE 2; H373 (Central nervous system, male reproductive organs) Aquatic Chronic 2; H411 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2.5
Substances with a workplace expe	ocure limit :	. ,,	
barium sulfate	7727-43-7		>= 30 -
	231-784-4		< 50

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin $\frac{1}{2}$

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon oxides
Phenolics
Sulphur oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 400001015910 1.3 21.06.2024 Date of first issue: 03.06.2016

Print Date 09.09.2024

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Repeated or prolonged skin contact may cause skin irritation

> and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Keep in properly

labelled containers.

Advice on common storage For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

2 - 40 °C

Further information on

storage stability

Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
barium sulfate	7727-43-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
bis-[4-(2,3- epoxipropoxi)phenyl]p ropane	Workers	Inhalation	Long-term systemic effects	4.93 mg/m3
	Workers	Dermal	Long-term systemic effects	0.75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.5 mg/kg bw/day
1,4-bis(2,3 epoxypropoxy)butane	Workers	Inhalation	Long-term systemic effects	4.7 mg/m3
	Workers	Dermal	Long-term systemic effects	6.66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.16 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.33 mg/kg bw/day
Formaldehyde, oligomeric reaction products with 1- chloro-2,3- epoxypropane and phenol (BPFDGE)	Workers	Dermal	Acute local effects	0.0083 mg/cm2
	Workers	Dermal	Long-term systemic effects	104.15 mg/kg
	Workers	Inhalation	Long-term systemic effects	29.39 mg/m3
	Consumers	Dermal	Long-term systemic effects	62.5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8.7 mg/m3
	Consumers	Oral	Long-term systemic effects	6.25 mg/kg bw/day
Reaction mass of bis(2,3-epoxypropyl)	Workers	Inhalation	Long-term systemic effects	0.025 mg/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

terephthalate and tris(oxiranylmethyl) benzene-1,2,4- tricarboxylate				
	Workers	Dermal	Long-term systemic effects	0.05 mg/kg bw/day
barium sulfate	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumer use	Inhalation	Long-term systemic effects	10 mg/m3
	Consumer use	Oral	Long-term systemic effects	13000 mg/kg

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value	
bis-[4-(2,3-	Fresh water	0.006 mg/l	
epoxipropoxi)phenyl]propane			
	Marine water	0.001 mg/l	
	Fresh water sediment	0.341 mg/kg dry	
		weight (d.w.)	
	Marine sediment	0.034 mg/kg dry	
		weight (d.w.)	
	Soil	0.065 mg/kg dry	
		weight (d.w.)	
	Sewage treatment plant	10 mg/l	
	Secondary Poisoning	11 mg/kg	
1,4-bis(2,3 epoxypropoxy)butane	Fresh water	0.024 mg/l	
	Remarks: Assessment Factors		
	Marine water	0.002 mg/l	
	Remarks: Assessment Factors		
	Sewage treatment plant	100 mg/l	
	Remarks:Assessment Factors		
	Fresh water sediment	0.084 mg/kg dry	
		weight (d.w.)	
	Remarks:Equilibrium method		
	Marine sediment	0.008 mg/kg dry	
		weight (d.w.)	
	Remarks:Equilibrium method		
	Soil	0.003 mg/kg dry	
		weight (d.w.)	
	Remarks:Equilibrium method		
	Oral	0.028 mg/kg	
Formaldehyde, oligomeric	Fresh water	0.003 mg/l	
reaction products with 1-chloro-			
2,3-epoxypropane and phenol			
(BPFDGE)			
	Remarks: Assessment Factors		
	Marine water	0 mg/l	
	Remarks: Assessment Factors		
	Intermittent use/release	0.0254 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	0.294 mg/kg dry	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

		weight (d.w.)
	Remarks:Equilibrium method	
	Marine sediment	0.0294 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Soil	0.237 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Sewage treatment plant	10 mg/l
	Remarks: Assessment Factors	
Siloxanes and silicones, di-Me, reaction products with silica	Fresh water sediment	> 100 mg/kg
·	Remarks: Assessment Factors	·
	Soil	23 mg/kg
	Remarks: Assessment Factors	•
Reaction mass of bis(2,3- epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene- 1,2,4-tricarboxylate	Fresh water	0.003 mg/l
	Remarks: Assessment Factors	
	Marine water	0 mg/l
	Remarks: Assessment Factors	
	Freshwater - intermittent	0.027 mg/l
	Remarks: Assessment Factors	·
	Sewage treatment plant	32 mg/l
	Remarks: Assessment Factors	
	Fresh water sediment	0.044 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	, ,
	Marine sediment	0.004 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	,
	Soil	0.007 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
barium sulfate	Fresh water	115 μg/l
	Sewage treatment plant	62.2 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	600.4 mg/kg
	Remarks: Assessment Factors	
	Soil	207.7 mg/kg
	Remarks: Assessment Factors	

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber Break through time : > 8 h

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Remarks : Gloves should be discarded and replaced if there is any

indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special

workplace conditions (mechanical strain, duration of contact).

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : beige

Odour : slight

Odour Threshold : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point/boiling range : > 200 °C

Flammability (solid, gas) : No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Upper explosion limit / Upper : No data is available on the product itself.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

flammability limit

Flash point : > 100 °C

Method: closed cup

Auto-ignition temperature : does not ignite

Decomposition temperature : > 200 °C

pH : ca. 7 (20 °C)

Concentration: 500 g/l

Viscosity

Viscosity, dynamic : 92,800 mPa.s (25 °C)

Method: Other guidelines

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Vapour pressure : < 1.33 hPa (20 °C)

Density : 1.6 g/cm3 (25 °C)

Relative density : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI Enriching lives through innovation

ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 400001015910 1.3 21.06.2024 Date of first issue: 03.06.2016

Print Date 09.09.2024

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

Remarks: No mortality observed at this dose.

LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

1,4-bis(2,3 epoxypropoxy)butane:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI Enriching lives through innovation

ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 400001015910 1.3 21.06.2024 Date of first issue: 03.06.2016

Print Date 09.09.2024

Acute oral toxicity : LD50 (Rat, male and female): 1,163 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Assessment: The component/mixture is moderately toxic after

single ingestion.

LC50 (Rat): > 2.068 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after short term inhalation., The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute dermal toxicity Acute toxicity estimate: 1,100 mg/kg

Method: Converted acute toxicity point estimate

Assessment: The component/mixture is moderately toxic after

single contact with skin.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Acute oral toxicity : LD50 (Rat, female): > 300 - < 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The component/mixture is moderately toxic after

single ingestion.

LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species Rabbit Exposure time 4 h

Assessment Irritating to skin.

Method **OECD Test Guideline 404**

Result Irritating to skin.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Species Rabbit

Method **OECD Test Guideline 404**

Result Irritating to skin.

1,4-bis(2,3 epoxypropoxy)butane:

Species Rabbit

Method **OECD Test Guideline 404**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Result : Skin irritation

GLP : yes

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Species : Rabbit

Assessment : Irritating to skin.

Method : No information available.

Result : Irritating to skin.

barium sulfate:

Species : human skin
Assessment : No skin irritation
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species : Rabbit

Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Result : Irritating to eyes.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rabbit

Assessment : Risk of serious damage to eyes.

Method : OECD Test Guideline 405

GLP : yes

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Species : Rabbit Assessment : Irritant

Method : OECD Test Guideline 405
Result : Normally reversible injuries

Species : Rabbit
Assessment : Corrosive

Result : Irreversible effects on the eye

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI Enriching lives through innovation

ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

barium sulfate:

Species Rabbit

Assessment No eye irritation

Method **OECD Test Guideline 405**

Result No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Test Type Local lymph node assay (LLNA)

Exposure routes Skin Species Mouse

Method **OECD Test Guideline 429**

Result The product is a skin sensitiser, sub-category 1B.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Test Type Local lymph node assay (LLNA)

Exposure routes Skin Species Mouse

Method **OECD Test Guideline 429**

Result May cause sensitisation by skin contact.

1,4-bis(2,3 epoxypropoxy)butane:

Exposure routes Skin **Species**

Guinea pig

Method **OECD Test Guideline 406**

Result May cause sensitisation by skin contact.

GLP yes

Assessment : Harmful if inhaled.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Exposure routes Skin **Species** Guinea pig

OECD Test Guideline 406 Method

Result May cause sensitisation by skin contact.

barium sulfate:

Exposure routes Skin Species Mouse

Method **OECD Test Guideline 429**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

Test Type: reverse mutation assay
Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay) Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Mouse (male)

Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test

Species: Rat (male) Cell type: Somatic Application Route: Oral

Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488

Result: negative

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Genotoxicity in vivo : Cell type: Somatic

Application Route: Oral Exposure time: 48 h Dose: 2000 mg/kg

Method: OECD Test Guideline 474

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Result: negative

Cell type: Somatic Application Route: Oral Dose: 2000 mg/kg

Method: OECD Test Guideline 486

Result: negative

1,4-bis(2,3 epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay

Concentration: 10 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Concentration: 1 - 100 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive GLP: no

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male) Cell type: Somatic Application Route: Oral Exposure time: 4 d Dose: 187.5 - 750 mg/kg

Method: OECD Test Guideline 474

Result: negative GLP: yes

Test Type: unscheduled DNA synthesis assay

Species: Rat Cell type: Liver cells Application Route: Oral

Method: OECD Test Guideline 486

Result: negative

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Germ cell mutagenicity-

Assessment

Weight of evidence does not support classification as a germ cell mutagen., Animal testing did not show any mutagenic

effects.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive GLP: yes

Test Type: gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive GLP: yes

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Mouse (male) Cell type: Germ Application Route: Oral Exposure time: 5 d Dose: 0 - 720 mg/kg

Method: OECD Test Guideline 483

Result: negative

Test Type: Chromosome aberration test in vitro

Species: Mouse (male)

Cell type: Germ

Application Route: Oral Exposure time: 5 d Dose: 0 - 360 mg/kg

Method: OECD Test Guideline 483

Result: negative

Test Type: Micronucleus test Species: Rat (male and female)

Application Route: Intraperitoneal injection

Dose: 2500 mg/kg

Method: OECD Test Guideline 474

Result: negative

Test Type: Micronucleus test Species: Rat (male and female)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Application Route: Intraperitoneal injection

Dose: 1500 mg/kg

Method: OECD Test Guideline 474

Result: negative

barium sulfate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species : Rat, male
Application Route : Oral
Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOAEL : 15 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Mouse, male Application Route : Dermal Exposure time : 24 month(s)

Dose : 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment : 3 days/week

NOEL : 0.1 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment : 5 days/week

NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Species : Rat, female

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week
NOAEL : 100 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, females

Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week
NOEL : 2 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

barium sulfate:

Species : Rat, male and female

Application Route : Oral
Exposure time : 104 weeks
Dose : 60 - 75 mg/kg
Method : OPPTS 870.4200

Result : negative

Species : Mouse, male and female

Application Route : Oral

Dose : 160 - 200 mg/kg Method : OPPTS 870.4200

Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily

General Toxicity - Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight

Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal : Species: Rabbit, female development : Application Route: Dermal

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

UK REACH HUNTSMAI

Enriching lives through innovation

ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Dose: 0, 30, 100 or 300 milligram per kilogram

Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: Other guidelines Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

Dose: 0, 20, 60 or 180 milligram per kilogram

Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0, 60, 180 and 540 milligram per kilogram

Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 180 mg/kg body weight Developmental Toxicity: NOAEL: > 540 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 mg/kg/ Duration of Single Treatment: 238 d General Toxicity - Parent: NOEL: 750

General Toxicity F1: NOEL: 750 mg/kg body weight General Toxicity F2: NOAEL: 750 mg/kg body weight

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

1,4-bis(2,3 epoxypropoxy)butane:

Effects on foetal : Test Type: Pre-natal development : Species: Rat, female

Application Route: Oral

Dose: 0/30/100/300 mg/kg bw/day Duration of Single Treatment: 17 d

General Toxicity Maternal: NOAEL: 300 mg/kg body weight

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Effects on fertility : Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

Dose: 0,3,15,30 milligram per kilogram Frequency of Treatment: 7 days/week

General Toxicity - Parent: NOAEC: 3 mg/kg body weight General Toxicity F1: NOAEC: 30 mg/kg body weight

Fertility: LOAEL: 15 mg/kg body weight

Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

Dose: 0,2.5,6,15 milligram per kilogram Frequency of Treatment: 7 days/week

General Toxicity - Parent: NOAEC: 15 mg/kg body weight General Toxicity F1: NOAEC: 15 mg/kg body weight

Fertility: NOAEL: 15 mg/kg body weight Method: OECD Test Guideline 443

GLP: ves

Effects on foetal development

Test Type: Embryo-foetal development

Species: Rat, females Strain: Sprague-Dawley Application Route: Oral

General Toxicity Maternal: NOEL: 60 mg/kg body weight Developmental Toxicity: NOEL: 60 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Reproductive toxicity -

Assessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments., Suspected of

damaging fertility.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Components:

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Exposure routes : Ingestion

Target Organs : Central nervous system, male reproductive organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Repeated dose toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species : Rat, male and female

NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks

Number of exposures : 7 d

Dose : 0, 50, 250, 1000 mg/kg/day Method : OECD Test Guideline 408

Species : Rat, male and female

NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

Number of exposures : 5 d

Dose : 0, 10, 100, 1000 mg/kg/day Method : OECD Test Guideline 411

Species : Mouse, male NOAEL : 100 mg/kg
Application Route : Skin contact Exposure time : 13 Weeks

Number of exposures : 3 d

Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Species : Rat, male and female

NOAEL : 250 mg/kg Application Route : Ingestion Exposure time : 13 Weeks

Number of exposures : 7 d

Method : Subchronic toxicity

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rat, male and female

NOAEL : 200 mg/kg Application Route : Oral Exposure time : 28 d Number of exposures : daily

Dose : 25, 100, 200, 400 mg/kg Method : Subacute toxicity

Species : Rat, male and female

NOAEL : 263 mg/kg
Application Route : Oral
Exposure time : 90 h
Number of exposures : daily

Dose : 0,30,100,300 mg/kg bw/day

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Method : OECD Test Guideline 408

GLP : yes

Remarks : Information given is based on data obtained from similar

substances.

Repeated dose toxicity -

Assessment

: Harmful if inhaled.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Species : Rat, male and female

NOEL : 75 mg/kg
NOAEL : 75 mg/kg
Application Route : Oral
Exposure time : 28 d

Method : OECD Test Guideline 407

Target Organs : Central nervous system, male reproductive organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

barium sulfate:

Species : Rat

LOEC : >= 104 mg/kg, 40 mg/m3

Application Route : Ingestion
Test atmosphere : dust/mist
Exposure time : 5 h
Number of exposures : 5 d

Method : Subchronic toxicity

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components

considered to have endocrine disrupting properties for human

health according to UK REACH Article 57(f),

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 : 11 mg/l Exposure time: 72 h

Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009

NOEC: 4.2 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test

Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 0.3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Toxicity to fish : LC50 (Fish): 2.54 mg/l

Exposure time: 96 h

Test substance: Fresh water Method: Calculation method

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.55 mg/l

Exposure time: 48 h

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

Method: Calculation method

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (green algae)): > 1.8 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes

Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: no

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water

GLP: no

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 0.3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 211

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

1,4-bis(2,3 epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l

End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203

GLP: no

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 75 mg/l

End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202

GLP: no

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 160

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209

GLP: no

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 8.8 mg/l

End point: mortality Exposure time: 96 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 81 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): > 2.72 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 0.368 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l

Exposure time: 3 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 209

M-Factor (Chronic aquatic : 1

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

toxicity)

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

barium sulfate:

Toxicity to fish : LC50 : 174 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 14.5 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 : > 100 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

NOEC: > 1.15 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 5.8 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)

pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

Degradation half life (DT50): 7.1 d (25 °C)

pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 3 mg/l Result: Not biodegradable Biodegradation: ca. 0 % Exposure time: 28 d

Method: Directive 67/548/EEC Annex V, C.4.E.

1,4-bis(2,3 epoxypropoxy)butane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 43 % Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

Test Type: aerobic

Inoculum: Sewage (STP effluent)

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 38 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 28 d

Method: OECD Test Guideline 301E

GLP: no

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not readily biodegradable.

Biodegradation: 52.4 % Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

12.3 Bioaccumulative potential

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Bioaccumulation : Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3.242 (25 °C)

octanol/water pH: 7.1

Method: OECD Test Guideline 117

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 150 Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 2.7 - 3.6

octanol/water Method: OECD Test Guideline 117

GLP: yes

1,4-bis(2,3 epoxypropoxy)butane:

Partition coefficient: n- : log Pow: -0.269 (25 °C)

octanol/water pH: 6.7

Method: OECD Test Guideline 117

GLP: yes

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Partition coefficient: n- : log Pow: 0.65 (20 °C)

octanol/water

12.4 Mobility in soil

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Distribution among : Koc: 445

environmental compartments

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (BPFDGE):

Distribution among : Koc: 4460

environmental compartments Method: OECD Test Guideline 121

1,4-bis(2,3 epoxypropoxy)butane:

Distribution among : Koc: 12.59

environmental compartments Method: OECD Test Guideline 121

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

 This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Components:

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 9

 RID
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo

: 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction : 964

(passenger aircraft)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

Packing instruction (LQ) Y964 Packing group Ш

Labels Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous yes

Environmentally hazardous yes

IMDG

Marine pollutant yes

IATA (Passenger)

Environmentally hazardous yes

IATA (Cargo)

Environmentally hazardous yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) Conditions of restriction for the

following entries should be

considered:

Number on list 3

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

This product does not contain substances of very high concern.

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL This product contains one or several components that are not

on the Canadian DSL nor NDSL.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

Version Revision Date: SDS Number: Date of last issue: 10.06.2022 1.3 21.06.2024 400001015910 Date of first issue: 03.06.2016

Print Date 09.09.2024

AIIC : Not in compliance with the inventory

ENCS : Notified. Allowed to be imported / manufactured only by the

notifiers. Please contact your Huntsman sales representative

for more information.

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Notified. Allowed to be imported / manufactured only by the

notifiers. Please contact your Huntsman sales representative

for more information.

TCSI : On the inventory, or in compliance with the inventory

TSCA : On or in compliance with the active portion of the TSCA

inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H361f : Suspected of damaging fertility.

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.06.2022

 1.3
 21.06.2024
 400001015910
 Date of first issue: 03.06.2016

Print Date 09.09.2024

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09,2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2014-2 HARDENER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Adhesives

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : HUNTSMAN ADVANCED MATERIALS (UK) LIMITED

Address : Ickleton Road, Duxford, Cambridgeshire

CB22 4XQ United Kingdom

Telephone : +41 61 299 20 41

E-mail address of person

responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333 Australia: 1800 786 152

New Zealand: 0800 767 437 USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage. Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

Hazard pictograms







Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/

doctor.

P391 Collect spillage.

Hazardous components which must be listed on the label:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction 2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction	-	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 30 - < 50

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

2,2,4(or 2,4,4)-Trimethylhexane- 1,6-diamine	25513-64-8 247-063-2	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318	>= 5 - < 10
		Skin Sens. 1A; H317	
Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine	68154-62-1 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2.5 - < 10
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	10563-29-8 234-148-4	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 specific concentration limit Skin Corr. 1A; H314 >= 29.85 % Skin Corr. 1B; H314 9.65 - < 29.85 % Skin Corr. 1C; H314 5 - < 9.65 %	>= 3 - < 5
Substances with a workplace exp	osure limit :		•
barium sulfate	7727-43-7 231-784-4		>= 30 - < 50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Sulphur oxides Carbon oxides

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023
1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Keep in properly

labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

: 2 - 40 °C

Further information on

storage stability

Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
barium sulfate	7727-43-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
N'-(3-aminopropyl)- N,N-dimethylpropane- 1,3-diamine	Workers	Inhalation	Long-term systemic effects	3.7 mg/m3
	Workers	Inhalation	Acute systemic effects	7.5 mg/m3
	Workers	Inhalation	Long-term local effects	3.7 mg/m3
	Workers	Inhalation	Acute local effects	7.5 mg/m3
	Workers	Dermal	Long-term systemic effects	0.67 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.65 mg/m3
	Consumers	Inhalation	Long-term local effects	0.65 mg/m3
	Consumers	Oral	Long-term systemic effects	0.2 mg/kg
2,2,4(or 2,4,4)-	Consumers	Oral	Long-term systemic	0.05 mg/kg

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023
1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

Trimethylhexane-1,6-diamine			effects	
barium sulfate	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumer use	Inhalation	Long-term systemic effects	10 mg/m3
	Consumer use	Oral	Long-term systemic effects	13000 mg/kg

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value	
N'-(3-aminopropyl)-N,N-	Fresh water	9.2 µg/l	
dimethylpropane-1,3-diamine			
	Remarks: Assessment Factors		
	Marine water	0.92 μg/l	
	Remarks: Assessment Factors		
	Freshwater - intermittent	92 µg/l	
	Remarks: Assessment Factors	· · ·	
	Sewage treatment plant	18.1 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	0.0336 mg/kg dry weight (d.w.)	
	Marine sediment	0.0034 mg/kg dry weight (d.w.)	
	Soil	0.0013 mg/kg dry weight (d.w.)	
Siloxanes and silicones, di-Me, reaction products with silica	Fresh water sediment	> 100 mg/kg	
	Remarks: Assessment Factors		
	Soil	23 mg/kg	
	Remarks: Assessment Factors		
2,2,4(or 2,4,4)-Trimethylhexane- 1,6-diamine	Fresh water	0.102 mg/l	
	Remarks: Assessment Factors		
	Marine water	0.01 mg/l	
	Remarks: Assessment Factors		
	Sewage treatment plant	72 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	0.662 mg/kg	
	Marine sediment	0.062 mg/kg	
barium sulfate	Fresh water	115 µg/l	
	Sewage treatment plant	62.2 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	600.4 mg/kg	
	Remarks: Assessment Factors		
	Soil	207.7 mg/kg	
	Remarks: Assessment Factors		

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water Tightly fitting safety goggles

Tightly fitting safety goggles

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Remarks : Gloves should be discarded and replaced if there is any

indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Equipment should conform to EN 14387

Filter type : Combined particulates, inorganic and acidic gas/vapour,

ammonia/amines and organic vapour type (ABEK-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : black

Odour : amine-like

Odour Threshold : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point : > 200 °C

Flammability (solid, gas) : No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

Flash point : > 100 °C

Method: closed cup

Auto-ignition temperature : > 200 °C

Decomposition temperature : > 200 °C

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : 75 - 150 Pas (20 °C)

Method: DIN, Other

Solubility(ies)

Water solubility : insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Vapour pressure : 0.001 hPa

Density : ca. 1.6 g/cm3

Relative density : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

9.2 Other information

Miscibility with water : immiscible

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18

(unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 (Rat): 910 mg/kg

Method: OECD Test Guideline 401

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Acute oral toxicity : LD50 (Rat, male and female): 1,669 mg/kg

Method: OECD Test Guideline 401

GLP: no

Assessment: The component/mixture is moderately toxic after

single ingestion.

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 435

Result : Irritating to skin.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : human skin

Assessment : May cause eye and skin irritation.

Method : OECD Test Guideline 431

Result : May cause eye and skin irritation.

Species : human skin Assessment : Irritant

Method : OECD Test Guideline 439

Result : Irritating to skin.

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rabbit

Assessment : Causes severe burns.

Result : Corrosive after 3 minutes or less of exposure

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : Irritating to skin.

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species : Rabbit

Assessment : Causes severe burns.

Method : OECD Test Guideline 404

Result : Extremely corrosive and destructive to tissue.

GLP : yes

barium sulfate:

Species : human skin
Assessment : No skin irritation
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Corrosive

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Corrosive

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH

Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023 1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : Irritating to eyes.

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Assessment Risk of serious damage to eyes. Result Risk of serious damage to eyes.

GLP no

barium sulfate:

Species Rabbit

No eye irritation Assessment

OECD Test Guideline 405 Method

Result No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Exposure routes Skin Species Mouse

Method **OECD Test Guideline 429**

Result The product is a skin sensitiser, sub-category 1A.

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Exposure routes Skin Species Guinea pig

Method **OECD Test Guideline 406**

Result The product is a skin sensitiser, sub-category 1A.

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Assessment : May cause sensitisation by skin contact.

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Test Type **Maximisation Test**

Exposure routes Skin Species Guinea pig

Probability or evidence of low to moderate skin sensitisation Assessment

rate in humans

Method OECD Test Guideline 406

Result Probability or evidence of low to moderate skin sensitisation

rate in humans

GLP : yes

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023 1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

barium sulfate:

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18

(unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Concentration: 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: Directive 67/548/EEC, Annex, B.13/14

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Concentration: 2 mg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Species: Chinese hamster (male and female)

Cell type: Bone marrow Application Route: Oral Dose: 825 - 1000 mg/kg

Method: OECD Test Guideline 474

Result: negative

Test Type: In vivo micronucleus test

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH

Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Revision Date: SDS Number: Date of last issue: 13.12.2023 Version 19.09.2024 400001014968 Date of first issue: 01.06.2016 1.6

Print Date 19.09.2024

Species: Mouse (male and female)

Application Route: Oral Dose: 850 - 1000 mg/kg

Method: OECD Test Guideline 474

Result: negative

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Genotoxicity in vitro Test Type: Chromosome aberration test in vitro

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative GLP: yes

Test Type: reverse mutation assay Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

GLP: ves

Test Type: reverse mutation assay

Test system: Salmonella tryphimurium and E. coli

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

barium sulfate:

Genotoxicity in vitro Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Mouse, male Species **Application Route** Dermal

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH

Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023
1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

Exposure time : 20 month(s)

Dose : 1.25/56.3 mg/animal

Frequency of Treatment : 3 daily

NOAEL : >= 56.3 mg/kg body weight

Result : negative

Remarks : Information given is based on data obtained from similar

substances.

barium sulfate:

Species : Rat, male and female

Application Route : Oral

Exposure time : 104 weeks

Dose : 60 - 75 mg/kg

Method : OPPTS 870.4200

Result : negative

Species : Mouse, male and female

Application Route : Oral

Dose : 160 - 200 mg/kg Method : OPPTS 870.4200

Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 422

Result: Animal testing did not show any effects on fertility.

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

Dose: 10, 60, 120 mg/kg bw/day Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal : Species: Rabbit, female development : Application Route: Oral

General Toxicity Maternal: NOAEL: 50,000 ppm

Result: No teratogenic effects

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Effects on fertility : Test Type: OECD Test Guideline 422

Species: Rat, male and female

Application Route: Oral

Dose: 5, 15 and 50 mg/kg bw/d

General Toxicity - Parent: NOAEL: 15 mg/kg body weight

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023 1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

General Toxicity F1: NOAEL: 15 mg/kg body weight

Method: OECD Test Guideline 422

Result: Animal testing did not show any effects on fertility.

GLP: yes

Effects on foetal

development

Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

Dose: 5, 15 and 50 mg/kg bw/d

General Toxicity Maternal: NOAEL: 15 mg/kg body weight Developmental Toxicity: NOAEL: 15 mg/kg body weight

Method: OECD Test Guideline 422

Result: Not classified

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

Species : Rat, male and female

NOAEL : 1000 mg/kg
Application Route : Ingestion
Exposure time : 6 Weeks
Number of exposures : 7 d

Method : Subacute toxicity

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rat, male and female NOAEL : 10 mg/kg bw/day

Application Route : Ingestion Exposure time : 13 Weeks Number of exposures : Daily

Dose : 10, 60, 180mg/kg bw

Target Organs : Liver

Species : Rat, male and female LOAEL : 60 mg/kg bw/day

Application Route : Ingestion
Exposure time : 13 Weeks
Number of exposures : Daily

Dose : 10, 60, 180mg/kg bw

Target Organs : Liver

Application Route

Test atmosphere

Exposure time

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species : Rat, male and female

500 mg/m3Inhalationvapour21 d 6 h

Number of exposures : 5 days/week
Dose : 550 mg/m3

Method : Subchronic toxicity

Remarks : Based on data from similar materials

Species : Mouse, male

NOAEL : >= 56.3 mg/kg/d

Application Route : Skin contact

Number of exposures : 3 d

Method : Chronic toxicity

Remarks : Based on data from similar materials

Species : Rat, male and female

NOAEL : 41 mg/kg
NOAEL : 1,000 mg/l, ppm
Application Route : oral (feed)
Exposure time : 20 months
Number of exposures : 3 times/week

Dose : 1000/7500/15000 ppm

Method : OECD Test Guideline 408

barium sulfate:

Species : Rat

LOEC : >= 104 mg/kg, 40 mg/m3

Application Route : Ingestion
Test atmosphere : dust/mist
Exposure time : 5 h

Number of exposures : 5 d

Method : Subchronic toxicity

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components

considered to have endocrine disrupting properties for human

health according to UK REACH Article 57(f),

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI

Enriching lives through innovation

ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023 19.09.2024 400001014968 Date of first issue: 01.06.2016 1.6

Print Date 19.09.2024

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18

(unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction:

LC50 (Brachydanio rerio (zebrafish)): 7.07 mg/l Toxicity to fish

> Exposure time: 96 h Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 5.18 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aguatic

plants

EC50 (Selenastrum capricornutum (green algae)): 2.43 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms EC50 (activated sludge): 421 mg/l

> Exposure time: 3 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 209

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Toxicity to fish LC50 (Leuciscus idus (Golden orfe)): 174 mg/l

> Exposure time: 48 h Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 31.5 mg/l

Exposure time: 24 h Method: DIN 38412

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (algae)): 43.5 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (algae)): 37.1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

SDS Number: Version Revision Date: Date of last issue: 13.12.2023 19.09.2024 400001014968 Date of first issue: 01.06.2016 1.6

Print Date 19.09.2024

NOEC (Pseudokirchneriella subcapitata (algae)): 16 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms IC50 (Pseudomonas putida): 89 mg/l

Exposure time: 17 h

Toxicity to fish (Chronic

toxicity)

NOEC: 10.9 mg/l

Exposure time: 30 d

Species: Brachydanio rerio (zebrafish) Method: OECD Test Guideline 210

Lowest Observed Effect Concentration: 10.9 mg/l

Exposure time: 30 d

Species: Brachydanio rerio (zebrafish) Method: OECD Test Guideline 210

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 1.02 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Lowest Observed Effect Concentration: 1.02 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Toxicity to soil dwelling

organisms

NOEC: >= 1,000 mg/kgExposure time: 56 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 222

EC50: >= 1,000 mg/kgExposure time: 56 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 222

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to fish LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

> End point: mortality Exposure time: 96 h Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 9.2 mg/l

End point: Immobilization

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI

Enriching lives through innovation

ARALDITE® 2014-2 HARDENER

SDS Number: Date of last issue: 13.12.2023 Version Revision Date: 19.09.2024 400001014968 Date of first issue: 01.06.2016 1.6

Print Date 19.09.2024

Exposure time: 48 h Test Type: static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): 21 mg/l Exposure time: 72 h

Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 201

GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 5.7 mg/l

Exposure time: 72 h Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms EC50 (Pseudomonas putida): 181 mg/l

Exposure time: 16 h Test Type: static test Analytical monitoring: no Test substance: Fresh water Method: DIN 38 412 Part 8

GLP: no

barium sulfate:

Toxicity to fish LC50: 174 mg/l

> Exposure time: 96 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 14.5 mg/l

Exposure time: 48 h Test Type: static test Test substance: Fresh water

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 : > 100 mg/lExposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

NOEC: > 1.15 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 5.8 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Biodegradability : Inoculum: activated sludge

Concentration: 11.4 mg/l

Result: Not readily biodegradable.

Biodegradation: 7 % Exposure time: 28 d

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Biodegradability : Test Type: aerobic

Result: Readily biodegradable.

Biodegradation: 100 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 28 d

Method: OECD Test Guideline 301A

Test substance: Fresh water

GLP: yes

12.3 Bioaccumulative potential

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Partition coefficient: n- : log Pow: -0.3 (25 °C)

octanol/water Method: OECD Test Guideline 117

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Partition coefficient: n- : log Pow: -0.56 (25 °C)

octanol/water pH: 11.6

Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09,2024

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

 ADR
 : UN 3082

 RID
 : UN 3082

 IMDG
 : UN 3082

 IATA
 : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(POLYAMIDE RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(POLYAMIDE RESIN)

14.3 Transport hazard class(es)

Class Subsidiary risks

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023 1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

 ADR
 : 9

 RID
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction : 964

(passenger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

Version Revision Date: SDS Number: Date of last issue: 13.12.2023 1.6 19.09.2024 400001014968 Date of first issue: 01.06.2016

Print Date 19.09.2024

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered: Number on list 3

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

This product does not contain substances of very high concern.

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AIIC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Based on product data or assessment

Eye Dam. 1 H318 Calculation method Skin Sens. 1 H317 Calculation method Aquatic Chronic 2 H411 Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® 2014-2 HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 13.12.2023

 1.6
 19.09.2024
 400001014968
 Date of first issue: 01.06.2016

Print Date 19.09.2024

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.